

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a method of evaluating a capillary pressure curve of the rocks of an underground reservoir from measurements on rock debris taken
5 therefrom.

Description of the Prior Art

Laboratory measurements on cores or cuttings

Measurement of petrophysical parameters such as the permeability, the porosity and the capillary properties on rock fragments obtained while drilling a well through an
10 underground formation is an interesting opportunity for operator companies to rapidly obtain a first petrophysical characterization of producing zones traversed by the well.

French Patent 2,809,821, filed by the assignee, describes a system of evaluating physical parameters such as the absolute permeability of porous rocks of an underground reservoir zone, from cuttings returned to the surface in the drilling mud. In
15 an enclosure where the cuttings are dipped in a viscous fluid, some of this fluid is injected at a pressure that increases with time until a predetermined pressure threshold is reached, so as to compress the gas trapped in the pores of the rock. This injection stage is followed by a relaxation stage where injection is stopped. The pressure evolution during the injection process is modelled from initial values selected for the physical
20 parameters of the cuttings. A computer adjusts the values iteratively so as to obtain the best possible agreement between the modelled pressure curve and the pressure curve really measured.

BEST AVAILABLE COPY

French patent application 02/0023, filed by the assignee, describes another method of evaluating physical parameters such as the absolute permeability and the porosity of the rocks of an underground reservoir zone, also from cuttings. An enclosure containing the rock fragments and filled with a viscous fluid communicates with a vessel
 5 containing the same fluid at a predetermined pressure so as to compress the gas trapped in the pores of the rock. The time of application of this pressure, according to whether it is short or long, allows measuring either of the pressure variation in the enclosure or the variation of the volume actually absorbed by the rock fragments. The pressure or volume evolution in the enclosure is then modelled from initial values selected for the
 10 physical parameters of the fragments, and the values of the physical parameters of the rock fragments are iteratively adjusted so that the modelled evolution best adjusts to the measured evolution of the physical parameter in the enclosure.

In the field of petrophysical study, the capillary pressure is also a very important datum for operators because it conditions :

- 15 - the initial distribution of the fluids in the reservoir from the aquifer zone (referred to as WOC, for water-oil contact, by those skilled in the art) to the upper part of the reservoir (transition zone). According to the capillary pressure curve associated with a reservoir rock and the nature of the fluids in place, this transition zone can extend over many meters , which has an important effect on the determination of the accumulations
 20 in place,
- the input pressure of a rock, which is particularly important for cap rocks. For example, for a gas storage tank, the input pressure of the cap rocks conditions directly the allowable overpressure in the storage levels without having leaks.

With the current techniques, the capillary pressure curve is obtained by means of laboratory measurements on reservoir cores. These methods are expensive because of the coring operations as well as the measurements on the cores, and the results are often available only several months after drilling.

5 *Approaches to rapidly obtain the capillary pressure curve*

However, there are alternative methods described in the literature for evaluating the capillary pressure curve rapidly, either during drilling or slightly later.

The most commonly used approach uses the mercury porosimetry technique for measuring the air/mercury capillary pressure curve P_c directly from cuttings. However,
10 the obtained curve is significantly different from the reference curve obtained from cores with high wetting fluid saturations. Further, this approach is based on the use of mercury, which is extremely polluting and progressively forbidden by the law in many countries, which poses a major problem for applying this technique in the near future.

Another known method uses the Nuclear Magnetic Resonance (NMR) technique to
15 rapidly estimate the capillary pressure curve from stratigraphic data measured in the well shortly after drilling. It is notably described in the following publications :

- Bowers, M., A. et al. : "Prediction Of Permeability From Capillary Pressure Curves Derived With NMR", 17 September 1998,
- Marshall, D., et al. : "Method For Correlating NMR Relaxometry And Mercury
20 Injection Data", SCA No. Society of Core Analysts International Symposium 1995,

- Volokitin, Y., W. J. et al. : "A Practical Approach To Obtain 1st Drainage Capillary Pressure Curves From NMR Core and Log Data", SCA No. Society of Core Analysts International Symposium 1999.

The NMR relaxation signal is first converted in terms of pore size distribution, then
 5 in terms of threshold size distribution, which allows calculation of a pseudo-capillary pressure curve. This approach has been tested on several samples of known curve P_c . The results show that a good agreement with the reference curves can only be obtained by means of a rigorous calibration stage to be carried out case by case according to the nature of the rocks studied. This calibration stage is necessary owing to the uncertainty
 10 on :

- the NMR signal-pore size distribution conversion which depends on the value of the surface relaxivity which is variable according to the rocks, and
- the pore size distribution-threshold size distribution conversion which depends on the nature of the rock and on the diagenesis process.

15 This approach is therefore not recommended in a predictive exploration context. In any case, it would not be applicable to cuttings.

Image analysis has also been the subject of work intended to obtain a curve P_c . The porous medium is first prepared in a form of a thin section photographed by a scanning electron microscopy or SEM. The image obtained is then analyzed so as to determine
 20 parameters representative of the proportion and of the shape of the voids in relation to the rock. In particular, it is possible to determine a threshold size distribution to reconstruct a pseudo-capillary pressure curve P_c . The main limitation of this method is the two-dimensional (2D) nature of the thin section, whereas the capillary pressure is by

definition a three-dimensional (3D) property. Besides, this technique requires quite heavy conditioning, which is not really compatible with a result obtained slightly later. Image analysis could be applicable to cuttings but it would require careful calibration to acquire a good predictability.

5 Finally, it can be noted that the centrifuging technique is sometimes applied in the field to cuttings in order to extract the largest possible amount of drilling fluid from the rock to minimize pollutant discharges to the environment and to limit the cost by recycling the drilling fluid recovered. The inventors do not know of centrifugation of cuttings having been considered in order to determine capillary properties.

10 SUMMARY OF THE INVENTION

The method according to the invention allows determination of the capillary pressure curve of rocks of an underground reservoir from measurements on rock debris or fragments (such as cuttings) taken therefrom, over the total saturation range of these rocks, within a short period and at a low cost, from these measurements. It comprises :

- 15 - measuring the permeability k of the rock debris;
- measuring the capillary pressure curve P_c as a function of the saturation of the rock debris initially saturated with a fluid by subjecting them to centrifugation; and
- parametrizing a capillary pressure curve P_c satisfying empirical relations depending on adjustable parameters, that is constrained to adjust to an asymptotic part of the
- 20 capillary curve measured by centrifugation, and to the value of permeability k measured on the cuttings, so as to obtain a whole capillary pressure curve.

Parametrizing the curve is advantageously carried out by selecting by default a set of the parameters allowing calibration on the asymptotic part of the capillary pressure P_c with low saturations, and by modifying the parameters step by step so that the estimation of the permeability given by one of the empirical relations used is best adjusted with the measurements of permeability k carried out on rock debris with the asymptotic part.

Permeability k of the cuttings is measured for example from measurements of the pressure variations in a vessel filled with a fluid containing the cuttings after it has been coupled for a predetermined period of time with a tank containing the same fluid under pressure, and from the volume actually absorbed by the cuttings, and from modelling the evolution of the pressure or of the volume in the vessel, from initial values selected for the physical parameters of the cuttings, which are iteratively adjusted so that the modelled pressure evolution best adjusts with the measured evolution of the physical parameters of the cuttings.

The method is notably advantageous in that it provides the capillary pressure of the rocks on the basis of simple cuttings that are more readily available and less expensive to obtain. The results are also obtained much more rapidly than with cores.

BRIEF DESCRIPTION OF THE DRAWINGS

Other features and advantages of the method according to the invention will be clear from reading the description hereafter of an embodiment given by way of non limitative example, with reference to the accompanying drawings wherein :

- Fig. 1 shows the evolution of the NMR signal during various centrifugation stages carried out on cuttings;

- Fig. 2A shows the curves P_c obtained on a single rock (B7) from cuttings and from a core;
- Fig. 2B shows the comparison between the reference curve P_c measured on a core and the reconstructed curve P_c over the total saturation range from the centrifugation measurements and the permeability measurement;
- Figs. 3A and 3B show results comparable to those shown in Figs. 2A and 2B respectively for another rock GDV1;
- Figs. 4A and 4B show results comparable to those shown in Figs. 2A and 2B respectively for another rock Rot1;
- Figs. 5A and 5B show results comparable to those shown in Figs. 2A and 2B respectively for another rock St Max;
- Fig. 6 shows the comparison between the reference permeabilities and the permeabilities measured on cuttings within the scope of the method described in the aforementioned French patent application 02/0023; and
- Fig. 7 diagrammatically shows the flowchart for implementing the method.

DETAILED DESCRIPTION OF THE INVENTION

The method intended for fast evaluation of a capillary pressure curve P_c from rock fragments or cuttings according to the invention is illustrated by Fig. 7. The method is based on two experimental measuring stages, followed by a parametrizing stage by reference with known curves, to reconstruct curve P_c over the total saturation range. During one of the measuring stages, capillary pressure data P_c are acquired by centrifuging the initially water-saturated rock fragments. The other experimental stage

allows calculation of the permeability value k of the rock from the method described in the aforementioned French patent application 02/0023. Reconstruction of curve P_c over the total saturation range is carried out by using a parametrized form. The parameters of the curve are determined in such a way that the curve matches the capillary pressure data P_c obtained experimentally and the estimated permeability value from the curve P_c obtained according to a known method such as Thomeer's or Swanson-Kamath's method, which are described below, with the value measured on the rock fragments. Several application cases are presented, with show the very good agreement obtained with reference curves without any particular previous calibration procedure.

10 **I) Measurement of P_c by centrifugation from the cuttings**

To implement the method, it is possible to use standard centrifugation means or more sophisticated means with automatic monitoring of the volumes of fluid produced, such as those described for example in patents EP-603,040 (US Patent 5,463,894), French patents 2,763,690, 2,772,477 (US patent 6,185,985) or 2,798,734 filed by the
15 assignee.

The cuttings which have come up to the surface during the drilling operation are first cleaned with solvents in a Soxhlet type device, then dried and saturated with 30 g/l brine. The cuttings are then drained in a damp cloth so as to remove the water trapped between the various cuttings d, then placed in a cell or cup fastened to the end of a
20 rotating arm. The water expelled by centrifugation from the cuttings flows through a grate and it is collected at the base of the cup. The experimental data are acquired in the same way as in the context of centrifugation on a core. For a centrifugation stage (given rotating speed), the evolution of the water production is measured until no significant

variation can be observed any longer, then the rotating speed is increased to start a new stage.

As can be seen in Fig. 1, a progressive decrease of the NMR signal and a shift to the short relaxation times T_2 are observed, which express a desaturation of the porous medium with the increase of the rotating speed. This type of measurement shows that there definitely is a capillary contact between the cuttings, which allows to measure P_c by centrifugation from cuttings.

The volume of water produced during the experiment is converted to saturation data from the volume of water initially contained in the cuttings. The latter is determined by weighing (difference in the weight of the cuttings before and after saturation) or directly by NMR measurement.

Figs. 2A to 5A show the result of experiments carried out from model cuttings, 1 to 2 mm in size, manufactured in the laboratory from rocks of known properties for which a curve P_c conventionally measured by centrifugation of a core is available. It can be seen that a good agreement is obtained with the reference curve at the level of the asymptotic part (low wetting fluid saturation). On the other hand, a big difference is observed for higher wetting fluid saturations. Results equivalent to those obtained within the context of porosimetry measurements using mercury on cuttings are thus obtained, without pollution risks.

The measured capillary pressure curve P_c is however representative only on the asymptotic part. A reconstruction procedure is therefore necessary to evaluate the behavior of the curve over the total saturation range.

II) Measurement of the permeability k of the cuttings

The method described in the aforementioned French patent application 02/02,242 is applied to measure the permeability of the cuttings. The cuttings are therefore dipped in a containment enclosure containing a viscous fluid. The enclosure is then coupled to a vessel containing the same fluid under pressure, so as to compress the gas trapped in the pores of the rock. According to a first embodiment, this communication period can be very short and followed, after a latency time, by the measurement of the pressure evolution in the enclosure. According to another embodiment, the communication period can be long enough to allow observing and measurement of the variation of the volume actually absorbed by the cuttings.

The evolution of the pressure or of the volume in the enclosure is then modelled from initial values selected for the physical parameters of the cuttings, and the values of the physical parameters of the cuttings are iteratively adjusted so that the modelled evolution best adjusts with the measured evolution of the physical parameter in the enclosure.

This procedure gives excellent results. The permeability values k of the cuttings are totally in accordance with the reference measurements obtained from cores.

III) Reconstruction of the total capillary pressure curve

In this third stage, the previous measurements are synthesized that have allowed construction of the asymptotic part of the capillary pressure curve P_c and the measurements of permeability k using empirical relations to model as well the physical parameters of rocks. The following publications :

- Thomeer, J.H.M. : “Introduction Of A Pore Geometrical Factor Defined By The Capillary Pressure Curve”, Trans AIME, vol. March, pp.73-77, 1960, and

- Thomeer, J.H.M. : “Air Permeability As A Function Of Three Pore Network Parameters”, Trans AIME, vol. April, pp.809-814, 1983

5 describe methods for evaluating the permeability from a capillary pressure curve. A capillary pressure curve P_c is modelled in the following form :

$$P_c = P_d \times \exp\left(-\frac{G}{\ln\left(\frac{V_b(P_c)}{V_b(P_\infty)}\right)}\right)$$

where :

- G is a shape parameter for accounting for the curvature of the capillary pressure
10 curve (related to the shape of the pore size distribution);
- P_d is the displacement pressure extrapolated to S_{Hg} equal to zero; and
- $V_{b\infty}$ is the percentage of volume occupied by the mercury at the end of the experiment at an infinite capillary pressure (equal to $\phi \times S_{Hg}$).

The three parameters of the model being related to the permeability by the
15 following expression :

$$k = 3.8068 \times G^{-1.334} \times \left[\frac{V_{b\infty}}{P_d} \right]^2$$

In the following publication :

- Swanson, B.F. : “A Simple Correlation Between Permeability And Mercury Capillary Pressures”, JPT, vol. December, pp.2498-2504, 1981,

the author proposes correlating the value of the permeability with the maximum value of ratio (V_b/P_c) on the mercury porosimetry curve. This particular point generally corresponds to the regime change that occurs at the end of the percolation regime, just before the significant capillary pressure increase. As regards the capacity of fluid flow in the porous medium, this point is particularly important because it represents the pore size for which the entire pore network is connected and which therefore controls the flow. The most general correlation provided by the author is given by the expression (Swanson 1981) :

$$k = 355 \times \left(\frac{V_b}{P_c} \right)_A^{2.005}$$

The following publication :

- Kamath, J. : "Evaluation Of Accuracy Of Estimating Air Permeability From Mercury Injection Data", SPE Formation evaluation, vol.7,4, pp.304-310, 1992

also relates to the comparative evaluation of the approaches using empirical correlation or physical models to determine the permeability value from a mercury porosimetry curve. The best agreement is obtained with a new correlation based on the aforementioned characteristic length by Swanson 1981, mentioned above :

$$\begin{aligned} k &= 413 \times L_{\max}^{1.85} & \text{if } k < 1mD \\ k &= 347 \times L_{\max}^{1.60} & \text{if } k > 1mD, \end{aligned}$$

L_{\max} being defined as follows :

$$L_{\max} = \left(\frac{\phi \times S_{nw}}{P_c} \right)_{\max} = \frac{\phi \times \lambda \times (100 - S_r)}{P_e \times (1 + \lambda)^{\frac{1}{\lambda} + 1}} \quad \text{and} \quad \left(\frac{P_e}{P_c} \right)^{\lambda} = \frac{S_w - S_r}{100 - S_r}$$

where :

- λ : exponent expressing the curvature of the capillary pressure curve (related to the shape of the pore size distribution),
- P_e : the displacement pressure extrapolated to S_{hg} equal to zero, and
- 5 - S_r : residual saturation occupied by the wetting fluid (%).

To parametrize the empirical capillary pressure curve P_c obtained from Thomeer's, Swanson's or Kamath's approaches, it is constrained to adjust to the asymptotic part obtained by centrifugation during the first stage of the method. The entire curve is constrained using also the value of permeability k measured on cuttings during the
 10 second stage of the method, which is compared with the result of the empirical relations. The parameters of the capillary pressure P_c are then modified until both the measured asymptotic behavior and the permeability estimation are met, which allows constraining the capillary pressure curve over the total saturation range S_w .

The inversion process starts with a set of default parameters which allow calibration
 15 of the asymptotic behavior of the capillary pressure P_c with low water saturations. These parameters are then modified step by step (mainly the input pressure P_e or P_d and the shape factor λ or G) so that the estimation of the permeability given by one of the previous relations is in good agreement with the permeability measurement obtained on cuttings while keeping a good agreement with the measurements of P_c at low water
 20 saturations.

1.1 Results obtained

Figures 2B, 3B, 4B and 5B show the comparison between the curve P_c reconstructed according to the previous procedure and the reference curve P_c obtained on a core. It

can be seen that, whatever the example considered, the reconstruction method allows obtaining a pertinent evolution of P_c over the total saturation range and in particular at high water saturations, whatever the permeability of the rock.

Name	K (mD)	G	Vb (fraction)	Pe (bar)
Rot1	150	0.28	0.89	0.38
GDV1	195	0.28	1.00	0.41
B7	780	0.25	0.92	0.2
StMax	2000	0.34	0.92	0.26

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.